(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 7 April 2005 (07.04.2005)

PCT

(10) International Publication Number WO 2005/031102 A1

(51) International Patent Classification⁷:

E06B 3/677

(21) International Application Number:

PCT/CA2004/001673

(22) International Filing Date:

27 September 2004 (27.09.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0322606.5 0327038.6 26 September 2003 (26.09.2003) GB 20 November 2003 (20.11.2003) GB

(71) Applicant and

(72) Inventor: AMBROSE, David, Howard [CA/CA]; 14940 Weston Road, King City, Ontario L7B 1K4 (CA).

(74) Agent: ASQUITH, Anthony; #28 - 461 Columbia Street West, Waterloo, Ontario N2T 2P5 (CA).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SYSTEM FOR ALLEVIATING IN-VAULT CONDENSATION IN DOUBLE-GLAZED WINDOWS



(57) Abstract: A hole is drilled through from the outside atmosphere Into the betweenpanes vault, and into the hole is inserted a normally-open valve assembly. The valve Is arranged to close responsively to the presence of a pressure differential in such direction that air would tends to enter the vault.

